


| Optical Spec    |                                   | 光学仕様                    |                   | Notice                                   |  | 特記       |            |                |
|-----------------|-----------------------------------|-------------------------|-------------------|--|--|----------|------------|----------------|
| Mag. 倍率         | $\times 2 \pm 0.06$ ( $\pm 3\%$ ) | Resolution 分解能          | 5.7 $\mu\text{m}$ | Compatible Camera : $\leq \frac{1}{2}$ " | CoC 許容錯乱円直径が $40\mu\text{m}$ の時  |          |            |                |
| W.D. 作動距離       | $65 \pm 1.95$ mm                  | Optical Distortion 光学歪み | 0.56 %            | Calculation conditions                   | D.O.F. = 0.34 mm   |          |            |                |
| Eff. F.No. 有効F値 | 16.9                              | TV Distortion テレビ歪み     | 0.18 %            | Compatible pixel : 10 $\mu\text{m}$      |  THIRD ANGLE PROJECTION 第三角法<br>UNIT : mm | SCALE 尺度 | DATE 日付    | MODEL NAME 機種名 |
| N.A. 開口数        | 0.059                             |                         |                   | Correspond $\lambda$ : 550 nm            |  | 1 : 1    | 2016.03.14 | HR-2F-65       |
| D.O.F. 被写界深度    | 0.25 mm                           |                         |                   | Correct Iris Stop : $\phi$ mm            |  |          |            |                |